

UV
Stabilised



Self-extinguishing



1250N
Compression
Strength



IP67
Ingress
Protection



Manufactured
in Australia


Australian manufactured heavy duty corrugated PVC conduit, designed with high compression strength for underground electrical installations. UV stabilised formulation suitable for outdoor applications. Tested and compliant to AS/NZS2053.5:2001. Certified to Best Environmental Practice Standards BEP PVC.

PROPERTIES

Minimum Operating Temperature	0°C
Maximum Operating Temperature	60°C
Flammability Rating UL94	V0 Self-extinguishing, non-flame propagating
Weatherability	Advanced UV Stabilisation formulation
Compression Strength	Minimum 1250N
Ingress Protection AS/NZS 1939	IP67 Rating
Standard Compliance	AS/NZS 2053.5:2001

DIMENSIONS

Part Number	i.d. (mm)	o.d. (mm)
CORR-20HDPVC	14	20
CORR-25HDPVC	19	25
CORR-32HDPVC	24.75	32
CORR-40HDPVC	32	40
CORR-50HDPVC	41.2	50



PACKAGING

Rolls
20m/50m
20m/50m
25m
10m/25m
10m

MANAGEMENT SYSTEMS



Manufactured in Australia under ISO9001:2015 certification and Best Environmental Practice Standards. All information contained in this document is given in good faith but without warranty. We reserve the right to make technical changes to this document without prior notice.

