



UV  
Stabilised



Self-extinguishing



750N  
Compression  
Strength



IP67  
Ingress  
Protection



Manufactured  
in Australia


Australian manufactured medium duty corrugated PVC conduit, designed for cost-effective flexible protection in a wide range of electrical installations. Advanced UV stabilisation formulation suitable for outdoor applications. Tested and compliant to AS/NZS2053.5:2001. Certified to Best Environmental Practice Standards BEP PVC.

### PROPERTIES

Minimum Operating Temperature	0°C
Maximum Operating Temperature	60°C
Flammability Rating UL94	V0 Self-extinguishing, non-flame propagating
Weatherability	Advanced UV Stabilisation formulation
TiO <sub>2</sub> Content	>1.5PHR
Compression Strength	Minimum 750N
Ingress Protection AS/NZS 1939	IP67 Rating
Standard Compliance	AS/NZS 2053.5:2001

### DIMENSIONS

Part Number	i.d. (mm)	o.d. (mm)
CORR-20MDPVC	14.3	20
CORR-25MDPVC	19.25	25
CORR-32MDPVC	25.4	32
CORR-40MDPVC	32.55	40
CORR-50MDPVC	41.6	50



### PACKAGING

Rolls
20m/50m
20m/50m
25m
10m/25m
10m

### MANAGEMENT SYSTEMS



Manufactured in Australia under ISO9001:2015 certification and Best Environmental Practice Standards. All information contained in this document is given in good faith but without warranty. We reserve the right to make technical changes to this document without prior notice.

