




Australian manufactured corrugated polyamide conduit, designed for cable protection and management in a wide range of automotive and industrial applications. Manufactured in a self-extinguishing formulation utilising a halogen-free flame-retardant system, producing a low smoke/low toxicity fire performance profile. Excellent chemical resistance to automotive oils, fluids and solvents. Extremely tough and durable with high impact strength and long fatigue life.

PROPERTIES

Minimum Operating Temperature	-40°C
Maximum Operating Temperature	120°C
Maximum Peak Operating Temperature	150°C
Flammability Rating UL94	V0 Self-extinguishing, non-flame propagating
Fire performance	Halogen-free, low smoke toxicity
Weatherability	UV Stabilised formulation
Ingress Protection AS/NZS 1939	IP67 Rating

DIMENSIONS

Part Number	i.d. (mm)	o.d. (mm)
NC08	6.4	10
NC10	8.5	11.5
NC12	9.9	13
NC16	12.8	15.9
NC20	16.6	21.2
NC25	21.2	25.3
NC32	29	33
NC40	36	42
NC50	48	54



PACKAGING

Spools
50/100m
50/100m
50/100m
50/100m
50/100m
50/100m
25/50m
25m
25m

MANAGEMENT SYSTEMS



Manufactured in Australia under ISO9001:2015 certification.. All information contained in this document is given in good faith but without warranty. We reserve the right to make technical changes to this document without prior notice.