



Very flexible



High impact resistance



Good chemical resistance



Lightweight protection



Manufactured in Australia

Australian manufactured corrugated polypropylene conduit, designed for cost-effective lightweight flexible protection in a wide range of automotive and industrial applications. Available in a standard or halogenated flame retardant version. Extremely tough and durable, using impact copolymer for high impact strength. Excellent resistance to automotive oils, fluids and solvents. Supplied in slit or unslit format depending on the requirements of the application. A wide range of custom packaging is accessible and custom colours are available on request.


PROPERTIES

Minimum Operating Temperature	-20°C
Maximum Continuous Operating Temperature	90°C
Maximum Peak Operating Temperature	120°C
Flammability UL94 (flame retardant version)	V2 Rating
Flammability UL94 (standard version)	HB Rating
Flammability rating FMVSS302	Pass
Weatherability	Moderate UV stability
RoHS status	Compliant

DIMENSIONS

PACKAGING

Part Number	i.d. (mm)	o.d. (mm)	Length
CORR-5PP	5	8	100/500m
CORR-7PP	7	10.4	3/10/30/50/100/200/400m
CORR-10PP	9.7	12.8	3/10/30/50/100/125/250m
CORR-13PP	12.6	15.7	3/10/30/75/100/150m
CORR-16PP	16.3	20.9	3/10/30/50/100m
CORR-20PP	21.1	25.2	10/30/50/100m
CORR-23PP	23	27	10/25/50m
CORR-29PP	29	33	10/25/50m
CORR-36PP	36	42	10/25m
CORR-48PP	48	54	10/25m



MANAGEMENT SYSTEMS



Manufactured in Australia under ISO9001:2015 certification. All information contained in this document is given in good faith but without warranty. We reserve the right to make technical changes to this document without prior notice.