




Australian manufactured corrugated HDPE conduit, designed for cost-effective flexible protection in a wide range of outdoor applications, including wind and solar farm installations. Uses an enhanced UV stabilisation formulation for optimum weathering performance and long-life outdoor performance. Extremely tough and durable with high impact strength. Excellent resistance to automotive oils, fluids and solvents. Supplied in slit or unslit format depending on the requirements of the application. A wide range of custom packaging is accessible and custom colours are available on request.

PROPERTIES

Minimum Operating Temperature	-50°C
Maximum Continuous Operating Temperature	80°C
Maximum Peak Operating Temperature	100°C
Flammability UL94	HB Rating
Weatherability	Excellent - Advanced UV Stabilisation Formulation
Carbon Black Content	2.2%
UV Formulation Standard Compliance	AS 61386 (14.2.3) & AS/NZS 4131

DIMENSIONS

Part Number	i.d. (mm)	o.d. (mm)
CORR-20HDPEUV	21.1	25.2
CORR-23HDPEUV	23	27
CORR-29HDPEUV	29	33
CORR-36HDPEUV	36	42
CORR-48HDPEUV	48	54



PACKAGING

Spool
50/100m
50m
50m
25m
25m

MANAGEMENT SYSTEMS



Manufactured in Australia under ISO9001:2015 certification. All information contained in this document is given in good faith but without warranty. We reserve the right to make technical changes to this document without prior notice.