

Excellent UV  
resistance



Highly flexible  
Fatigue resistant



Good chemical  
resistance



High impact  
resistance



Manufactured  
in Australia


Australian manufactured corrugated polypropylene conduit, designed for cost-effective flexible protection in a wide range of outdoor applications including wind and solar farm installations. Uses an enhanced UV stabilisation formulation for optimum weathering performance and long-life outdoor performance. Extremely tough and durable, using impact copolymer for high impact strength. Excellent resistance to automotive oils, fluids and solvents. Supplied in slit or unslit format depending on the requirements of the application. A wide range of custom packaging is accessible and custom colours are available on request.

### PROPERTIES

Minimum Operating Temperature	-20°C
Maximum Continuous Operating Temperature	90°C
Maximum Peak Operating Temperature	120°C
Flammability UL94	HB Rating
Weatherability	Excellent - Advanced UV Stabilisation Formulation
Carbon Black Content	2.2%
UV Formulation Standard Compliance	AS 61386 (14.2.3) & AS/NZS 4131

### DIMENSIONS

Part Number	i.d. (mm)	o.d. (mm)
CORR-20PPUV	21.1	25.2
CORR-23PPUV	23	27
CORR-29PPUV	29	33
CORR-36PPUV	36	42
CORR-48PPUV	48	54



### PACKAGING

Part Number	Spool
CORR-20PPUV	50/100m
CORR-23PPUV	50m
CORR-29PPUV	50m
CORR-36PPUV	25m
CORR-48PPUV	25m

### MANAGEMENT SYSTEMS



Manufactured in Australia under ISO9001:2015 certification. All information contained in this document is given in good faith but without warranty. We reserve the right to make technical changes to this document without prior notice.